LADDER TYPE CABLE TRAY:



WIDTH: 150 mm to 900 mm
HEIGTH: 50 mm to 150 mm
THICKNESS: 1.60 mm to 3.0 mm
LENGTH: 2.5 mtr to 3.0 mtr

MATERIAL

• HR Sheet: As per IS:1079, IS:2062 & IS:10748

• GP Sheet: As per IS:277

HOT DIP GALVANISING : As per IS:4759 & IS:2629

HARDWARE: As per IS:1367 4.6 Grade

PERFORATED CABLE TRAY:



WIDTH : 150 mm to 900 mm HEIGTH : 50 mm to 150 mm THICKNESS : 1.60 mm to 3.0 mm LENGTH : 2.5 mtr to 3.0 mtr

MATERIAL

• HR Sheet: As per IS:1079, IS:2062 & IS:10748

• GP Sheet: As per IS:277

HOT DIP GALVANISING : As per IS:4759 & IS:2629 **HARDWARE :** As per IS:1367 4.6 Grade

ACCESSORIES FOR LADDER TRAY:



HORIZONTAL BLEND



VERTICAL BLEND



REDUCER



HORIZONTAL TEE

ACCESSORIES FOR PERFORATED CABLE TRAY:



ELBOW



TEE



VERTICAL INNER



HORIZONTAL PERFORATED

RACEWAYS:



RACEWAYS



RACEWAYS WITH COVER



RACEWAYS WITH PARTITION



SAFETY HELMET



SAFETY JACKETS



LEATHER BELT SET WITH TOOLS



SAFETY HARNESS



SAFETY-GOGGLES



SAFETY SHOES



PROTECTIVE GLOVES



MEASURING TAPE



SPIRIT LEVELLERS



